



OH320-CC Series Ultra Stable OCXO

CONNOR WINFIELD



2111 Comprehensive Drive

Aurora, Illinois 60505

Phone: 630-851-4722

Fax: 630-851-5040

www.conwin.com

Description:

Connor-Winfield's Series OH320-CC is a high precision Enhanced Oven Compensated Crystal Oscillator (OCXO) in a small 22x25.4mm surface mount package. The OH320-CC Series provides thermal stability of less than ± 1 ppb and is designed for applications demanding excellent frequency stability and excellent phase noise.



Features:

- Output Frequency: 10.0, 12.8, 20.0, 25.0, or 100.0 MHz
- 3.3 or 5.0 Vdc Operation
- 22 x 25.4 mm SMT Package
- Frequency Stabilities: ± 1 ppb or ± 0.5 ppb
- Temperature Ranges: -40 to 85°C or -20 to 70°C
- CMOS or Sine Output
- Grounded Metal Cover
- RoHS Compliant / Lead Free

Absolute Maximum Ratings

Parameter	Minimum	Nominal	Maximum	Units	Notes
Storage Temperature	-55	-	105	$^{\circ}\text{C}$	
Supply Voltage (Vcc)	-0.5	-	5.5	Vdc	
Operating Supply Voltage 3.3V	3.135	3.30	3.465	Vdc	
Operating Supply Voltage 5.0V	4.75	5.0	5.25	Vdc	

Absolute Ratings: Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only. The functional operation of the device at those or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to conditions outside the "recommended operating conditions" for any extended period of time may adversely impact device reliability and result in failures not covered by warranty.

Operating Specifications

Parameter	Minimum	Nominal	Maximum	Units	Notes
Center Frequency (Fo)	10.0, 12.8, 20.0, 25.0, or 100.0			MHz	
Operating Temperature					
Option 6	-40	-	85	$^{\circ}\text{C}$	
Option 7	-20	-	70	$^{\circ}\text{C}$	
Frequency Calibration @ 25°C	-200	-	200	ppb	
Frequency Stability vs. Temperature					
Option 01	-1.0	-	1.0	ppb	1
Option 005	-0.5	-	0.5	ppb	1
Frequency vs. Supply Voltage	-0.2	-	0.2	ppb	Vcc $\pm 1\%$
Frequency vs. Load	-0.2	-	0.2	ppb	Vcc $\pm 1\%$
Aging: Daily	-0.5	-	0.5	ppb/day	2
Aging: First Year	-50	-	50	ppb	
Lifetime Tolerance: (20 years)	-400	-	400	ppb	3
Supply Voltage (Vcc)					
Option 03	3.135	3.30	3.465	Vdc	4
Option 05	4.75	5.0	5.25	Vdc	4
Power Consumption:					
Steady State, @ 25°C , 3.3Vdc	-	-	1.5	W	5
Turn On 3.3Vdc	-	-	3.6	W	5
Steady State, @ 25°C , 5.0Vdc	-	-	2.5	W	5
Turn On 5.0Vdc	-	-	4.2	W	5
Phase Jitter: (BW: 10 Hz to Fo/2)	-	-	1.0	ps rms	
Allan Deviation (Tau=10s) for Fo=10MHz	-	2.0E-12	1.0E-11		
Start-Up Time:	-	-	500	ms	
Warm Up Time: @ 25°C	-	-	5	minutes	6





Phase Noise

Parameter	Minimum	Nominal	Maximum	Units	Notes
SSB Phase Noise at 1Hz offset	-	-90	-85	dBc/Hz	
SSB Phase Noise at 10Hz offset	-	-120	-115	dBc/Hz	
SSB Phase Noise at 100Hz offset	-	-140	-140	dBc/Hz	
SSB Phase Noise at 1KHz offset	-	-154	-150	dBc/Hz	
SSB Phase Noise at 10KHz offset	-	-260	-155	dBc/Hz	
SSB Phase Noise at 100KHz offset	-	-163	-160	dBc/Hz	

CMOS Output Characteristics

Parameter	Minimum	Nominal	Maximum	Units	Notes
Load	-	15	-	pF	
Output Voltage: High (Voh)	3.0	-	-	V	
Output Voltage: Low (Vol)	-	-	0.4	V	
Output Current: High (Ioh)	-0.4	-	-	mA	
Output Current: Low (Iol)	-	-	0.4	mA	
Duty Cycle at 50% of Vcc	45	50	55	%	
Rise / Fall Time: 10% to 90%	-	-	6	ns	
Spurious Output	-	-	-80	dBc	

Sinewave Output Characteristics

Parameter	Minimum	Nominal	Maximum	Units	Notes
Load	-	50	-	Ohms	
Output Power	5	7	9	dBm	
Harmonics	-	-	-40	dBc	
Spurious	-	-	-70	dBc	

Notes:

1. Frequency stability is based on $(F_{max}-F_{min})/2$.
2. At time of shipment after 48 hours of operation.
3. Inclusive of Calibration, Operating Temperature, Supply Voltage change, Load change, and 10 Year Aging.
4. Supply voltage must reach Vcc levels monotonically within a ramp-up time of <12 ms.
5. Measured with Vcc = Nominal in calm air.
6. Measured @ 25°C, within ±100 ppb, referenced one hour after turn-on.

Re-Stabilization Time

Off Time	Re stabilization Time
<1 Hour	<2 Hours *
<6 Hour	<12 Hours *
<24 Hour	<48 Hours *
1 to 16 Days	48 Hours + 1/4 Off Time *
>16 Days	<6 Days *

* For a given off time, the time required to meet daily aging, short term stability requirements.



Attention: System Designers please review Application Note AN2093:
System Design Information and Printed Circuit Board Layout Guidelines for OCXO Oscillators.
@ www.conwin.com/support.html

Bulletin	Cx309
Page	2 of 6
Revision	03
Date	27 Feb 2024



Package Characteristics

OH320 Package Package consists of a hermetic metal package OCXO mounted to an FR4 substrate surrounded by a non-hermetic metal cover (airflow shield)

Environmental Characteristics

Shock	500 G's 1ms, Halfsine, 3 shocks per direction, per MIL-STD 202G, Method 213B Test Condition D.
Sinusoidal Vibration	0.06" D.A. or 10G's Peak, 10 to 500 Hz, per MIL-STD-202G, Method 204D, Test Condition A.
Random Vibration	5.35 G's rms. 20 to 2000 Hz per MIL-STD-202G, Method 214, Test Condition 1A, 15 minutes each axis.
Moisture	10 cycles, 95% RH, Per MIL-STD-202G, Method 112.
Marking Permanency	Per MIL-STD-202G, Method 215J.
Solder Process Recommendations:	RoHS compliant, lead free. See solder profile on page 5.
In-line reflow:	Refer to recommended reflow pre-heat and reflow temperatures on page 5. Package material consists of metal cover with FR4 substrate. Component solder is Pb-free high temperature eutectic alloy with melting point of 221°C. Product should not be inverted during reflow.
Removal of device:	If for any reason the device needs to be removed from the board, use a temperature controlled repair station with profile monitoring capabilities. Following a monitored profile will insure the device is properly pre-heated prior to reflow. Refer to IPC 610E for inspection guidelines.
Recommended Cleaning Process:	(If required)

Device is non-hermetic, water resistance with four weep holes, one in each corner to allow moisture to be removed during the drying cycle. We recommend in-line warm water wash with air knife and drying capabilities. If cleaner does not have drying capability, then use hot air circulated oven. Boards should be placed in the oven vertically for good water runoff

Device must be dried properly prior to use!

Note: If saponifier is used make sure the device is rinsed properly to insure all residues are removed. PH of saponifier should not exceed 10.

Drying Temperature: Between 85 to 100°C.

Drying Time: Time will vary depending on the board size.

Caution: Do not submerge the device!

Ordering Information

OH320-CC Oscillator Series Enhanced Stability OCXO	7 Temperature Range 6 = -40 to 85°C 7 = -20 to 70°C	005 Stability 01 = ±1.0 ppb 005 = ±0.5 ppb	03 Supply Voltage 03 = 3.3V 05 = 5.0V	CF Output Type Fixed CF = CMOS SF = SINE	10.0 MHz Frequency 10.0, 12.8, 20M, 25M, 100 MHz
---	---	--	---	--	--

** Not all options available at Digi-Key


Part Number Example: OH320-CC-700503CF-010.0M




Attention: System Designers please review Application Note AN2093:
System Design Information and Printed Circuit Board Layout Guidelines for OCXO Oscillators.
@ www.conwin.com/support.html

Bulletin	Cx309
Page	3 of 6
Revision	03
Date	27 Feb 2024

Package Outline




Suggested Pad Layout



* Do not route any traces in the keep out area. It is recommended the next layer under the keep out area is to be ground plane.

Marking Information




Date Code (YYWW)
Model Number
Output Frequency
Serial # Barcode
Serial Number

Pad Connections

Pad	Connection
1:	N/C
2:	Do not Connect
3:	Supply Voltage (Vcc)
4:	RF Output
5:	Do Not Connect
6:	Do Not Connect
7:	Ground

DO NOT connect "DNC" pads to ground or supply rails.


Test Circuit - CMOS Output




Attention: System Designers please review Application Note AN2093:
System Design Information and Printed Circuit Board Layout Guidelines for OCXO Oscillators.
www.conwin.com/support.html

Bulletin	Cx309
Page	4 of 6
Revision	03
Date	27 Feb 2024


Test Circuit Sinewave Output



Frequency Stability Plot over Temperature



Solder Profile




Meets IPC/JEDEC J-STD-020C

ADEV Plot

Allan Deviation $\sigma_y(\tau)$




TDEV & MTIE 4-Day Stability Measurement Through HPF (1MHz)



Trace	Notes	Input Freq	Sample Interval	AVG at fs	Duration	Acquired	Instrument
ETHDC280383CF 6.10MHz @ COVERED Weekend (Innovat)	CMAC 00.03	10.000 MHz	1 s	2.57E-12	24.0h Run 0s	172800 pts	Microsemi 3102A

Tape and Reel Information

MEETS EIA-481A AND EIAJ-1009B
100 PCS/REEL MAXIMUM



Revision History

Revision	Date	Changes
00	12/05/19	Initial Release
01	10/28/20	Change part number series name
02	12/22/20	Update stability specifications, added Tape and Reel drawings
03	02/27/24	Update phase noise, reflow recommendations, and add Digi-Key availability.

Bulletin	Cx309
Page	6 of 6
Revision	03
Date	27 Feb 2024