

# 3.3V Surface Mount 3.2mm x 5.0mm Oscillators V7123 & V7133 Series

# CONNOR WINFIELD



## Features:

RoHS Compliant  
3.3V Operation  
Small Surface Mount Package:  
5.0mm x 3.2mm x 1.2mm  
Overall Frequency Tolerance:  
V7123:  $\pm 50$ ppm  
V7133:  $\pm 100$ ppm  
Low Jitter < 1pS RMS  
Temperature Range -10° to 70°C  
Enable / Disable Pad 6  
Tape and Reel Packaging

## VCXO

The Connor-Winfield, RoHS compliant, V7123 and V7133 are hermetically sealed, Surface Mount, 3.3V Voltage Controlled Crystal Oscillators (VCXO) with Tri-State Enable/Disable function on pad 6. The V7123 and V7133 are designed for phased lock loop applications requiring low jitter and tight stability.

2111 Comprehensive Drive  
Aurora, Illinois 60505  
Phone: 630-851-4722  
Fax: 630-851-5040  
**www.conwin.com**  
US Headquarters:  
630-851-4722  
European Headquarters:  
+353-61-472221

## Absolute Maximum Ratings

Parameter	Minimum	Nominal	Maximum	Units	Notes
Storage Temperature	-55	-	125	°C	
Supply Voltage (Vcc)	-0.5	-	7.0	Vdc	
Control Voltage (Vc)	-0.5	-	Vcc	Vdc	

## Operating Specifications

Parameter	Minimum	Nominal	Maximum	Units	Notes
Frequency Range (Fo)	2.0	-	52	MHz	
Frequency Tolerance Model V7123 Model V7133	-50 -100	- -	50 100	ppm	1
Operating Temperature Range	-10	-	70	°C	
Supply Voltage (Vcc)	3.135	3.3	3.465	Vdc	
Supply Current (Icc) 1.0 to 29,999 MHz 30 to 52 MHz	- -	- -	15 25	mA	
Jitter: (BW=12kHz to 20 MHz) (BW=10Hz to 20 MHz)	- -	- -	1 5	ps RMS	

## Input Characteristics

Parameter	Minimum	Nominal	Maximum	Units	Notes
Control Voltage Range (Vc)	0.15	1.65	3.15	Vdc	
Frequency Pullability @ 25°C	$\pm 100$	-	-	ppm	
Monotonic Linearity	-10	-	10	%	
Input Impedance	-	50K	-	Ohm	
Modulation Bandwidth (3dB)	10	-	-	KHz	
Enable Input Voltage - High (Vih) Disable Input Voltage - Low (Vil)	2.7 -	- -	- 0.3	Vdc	2

## LVC MOS Output Characteristics

Parameter	Minimum	Nominal	Maximum	Units	Notes
Load	-	-	15	pf	
Voltage High (Voh) Low (Vol)	2.7 -	- -	- 0.33	Vdc	
Current High (Ioh) Low (Iol)	-1 -	- -	- 4	mA	
Duty Cycle at 50% of Vcc	40	50	60	%	
Rise / Fall Time 20% to 80%	-	-	5	nS	
Start-up Time	-	-	10	mS	

## Notes:

1. Referenced to (Fo) measured with control voltage @ 2.5Vdc. Inclusive of frequency vs. temperature stability, supply voltage/load change, shock and vibration, 15 years aging.
2. The Output is enabled with no connection on the enable pin. Output is at high impedance when disabled.



Bulletin **Vx469**  
Page **1 of 2**  
Revision **01**  
Date **03 April 2007**

### Package Characteristics

Package	Hermetically sealed, ceramic leadless package.
---------	--

### Environmental Characteristics

Temperature Cycle	The specimen shall meet electrical characteristics after tested 5 cycles of -55°C / 30 minutes and +125°C / 30 minutes
Hermetical	No bubbles appear in Flourinert (FC-43) at 125°C ±5°C for 5 minutes
Solvent Resistance	Marking will withstand immersion in Isopropyl Alcohol or Trichloroethylene


### Soldering

General Conditions	260°C max x 10 sec max x 2 times max or 230°C max x 180 sec max x 1 time
Typical Operation Data (Vapor phase reflow)	20 to 100 sec up to 215°C, 50 sec at 215°C, then down to room temperature per 1 to 5°C / sec

### Mechanical Characteristics

Free Drop	The specimen shall meet electrical characteristics after tested 3 times, Free Drop testing on the hard wooden board from a height of 75 cm.
Vibration	The specimen shall meet electrical characteristics after tested by the following conditions: 10-55Hz 1.5mm Amplitude, 55-2000 Hz 20 G's, 2 hours for each plane
Thermal Shock	After applied Thermal Shock of 245°C max x 10 sec max x 2 times, or 215°C max x 180 sec max, the specimen shall meet electrical characteristics
Solderability	(EIAJ-RCX-0102/101 Condition 1a) 1) Flux: MIL-F-14256 (WW Rosin=25%, Isopropyl Alcohol = 75%) 2) Solder: QQ-S-571 (Sn = 63%, Pb = 37%) 3) Solder bath temperature: 235°C ±5°C 4) Depth of immersion: Up to electrical terminal 5) Immersing time: Within 2 sec ±0.5 sec into solder bath


**After performing the above procedures, a newly soldered coverage shall be greater than 90%**




### Pin Function

- 1: Control Voltage
- 2: Ground
- 3: Ground or No Connection
- 4: Output
- 5: Vcc
- 6: Tri-State Enable/Disable


### Tape and Reel Dimensions




### Suggested Pad Layout




### Test Circuit



### Output Waveform



### Solder Profile



### Ordering Information

**V7123 - 051.84M**

VCXO SERIES CENTER FREQUENCY

Bulletin	<b>Vx469</b>
Page	<b>2 of 2</b>
Revision	<b>01</b>
Date	<b>03 April 2007</b>